

Mercoird 123 Series Nomenclature				
EXAMPLE	123	2		123-2 Liquid Level Control with SPST mercury switch closing on level increase, minimum specific gravity 0.88, cast iron body, general purpose case, switch rated at 10 amp 120 VAC/DC, 5 amp 24 VAC/DC, pressure rating 150 psi (10 bar), maximum process temperature 365°F (185°C).
CONNECTION	123			Single Stage, Automatic Reset, Brass Trim, NEMA 1
	123XLW			Replacement Float, Cap, and Switch Assembly Only, No chamber for 123
	123RU			Single Stage, Manual Reset, Brass Trim, NEMA 1
	123RL			Single Stage, Manual Reset, Brass Trim, NEMA 1
	123RUXLW			Replacement Float, Cap, and Switch Assembly Only, No chamber for 123RU
	123RLXLW			Replacement Float, Cap, and Switch Assembly Only, No chamber for 123 RL
	123XLS			Replacement Switch Assembly Only for 123
CIRCUITS		2		9-51 NC SPST Mercury Switch
		3		9-51 NO SPST Mercury Switch
		103		(2) 9-51 NO DPST Mercury Switch
		127		(2) 9-51 NO DPST Mercury Switch
		151V		(2) 9-35 4-wire SPST Vibration Dampened Mercury Switch
		152		9-62 4-wire SPST Mercury Switch
		153		9-64 3-wire SPDT Mercury Switch
		156		(2) 9-51 4-wire SPST Mercury Switch
		160		9-61 NO SPST & 9-51 NC 4-wire SPST Mercury Switch
		162		9-51 NO 4-wire SPST & 9-61 NC SPST Mercury Switch
		702		9-51 NO SPST & 9-64 3-wire SPDT Mercury Switch
		705		9-51 NO SPST & 9-64 3-wire SPDT Mercury Switch
		729		9-64 3-wire SPDT Mercury Switch
		804		(2) 9-64 DPDT Mercury Switch
		7000-153		SPDT Snap Switch
OPTIONS			STW	Stainless steel tag wiring
			23720	Fungus proofing special 23720
			440V	440 volt option for circuits