

Mercoird 125 Series Nomenclature				
EXAMPLE	125	4820		125-4820 Liquid Level Control with SPST mercury switch closing on level fall, minimum specific gravity 0.88, cast iron body, general purpose case, switch rated at 10 amp 120 VAC/DC, 5 amp 24 VAC/DC, pressure rating 150 psi (10 bar), maximum process temperature 365°F (185°C).
CONNECTION	125			Two Stage, Automatic Reset, Brass Trim, NEMA 1
	125XLW			Replacement Float, Cap, and Switch Assembly Only, No chamber for 125
	125XLS			Replacement Switch Assembly Only for 125
CIRCUITS		4806		(2) 9-64 6-wire DPDT Mercury Switch
		4810		9-64 3-wire SPDT Mercury Switch
		4814		(2) 9-51 NO DPST Mercury Switch
		4815		(2) 9-51 4-wire SPDT Mercury Switch
		4820		9-51 NC SPST Mercury Switch
		4821		9-51 NO SPST Mercury Switch
		4822		Consult factory for details.
		4823		2 Stage Control, (2) 9-51 Mercury Switches
		4828		(2) 9-35AV 4-wire SPDT Mercury Switch
		4829		Consult factory for details.
		4831		2 Stage Control, (2) 9-51 NO SPST Mercury Switches
		4849		2 Stage Control, (2) 9-51 NO SPST Mercury Switches
		4853		2 Stage Control, (2) 9-64 3-wire SPDT & (1) 9-51 NO SPST
		4855		2 Stage Control, (2) 9-64 3-wire SPDT & (1) 9-51 NC SPST
		4857		Consult factory for details.
		5822		Consult factory for details.
	5823		2 Stage Control, (2) 9-51 Mercury Switches	
	5831		2 Stage Control, (2) 9-51 NO SPST Mercury Switches	
	5849		2 Stage Control, (2) 9-51 Mercury Switches	
OPTIONS			STW	Stainless steel tag wiring
			23720	Fungus proofing special 23720
			2507	440 volt option for circuits